



DOMESTIC HOT WATER TANKS CLASS A WITH TWO HEAT EXCHANGERS

EV 7/5 S2 200 65 A PS

SAP Code	305629
Capacity	192 L
Net weight	73 kg
Insulation	75 mm
Heat exchanger surface S1	0.75 m ²
Heat exchanger surface S2	0.54 m ²
Heat exchanger capacity S1	4.6 L
Heat exchanger capacity S2	3.3 L
Heat losses ΔT 45K	41 W
Energy class	A
Maximum operational temperature	95 °C
Maximum operational temperature of the heat exchanger	110 °C
Rated pressure of the water tank	8 bar



Rated pressure of the heat exchanger	6 bar
V40 - hot water delivered with a temperature of at least 40°C (S1)	280 L
V40 - hot water delivered with a temperature of at least 40°C (S2)	136 L
Diameter	650 mm



Information

EV 7/5 S2 200 65 A PS

- **HIGHLY EFFICIENT INSULATION** compliant with latest industry regulations – ERP Class A
- High quality **ENAMEL COATING** with **TESY CrystalTech PRO** technology.
- **MAGNESIUM ANODES PROTECTION** of the inner tank surface for extended product life.
- **SERVICE OPENING** for easy inspection and maintenance.
- Option for **INSTALLATION** of different power rated **HEATING ELEMENTS**.
- Thermoregulator installation pocket.
- Pockets for thermo sensors.

Serie information

EV 7/5 S2 200 65 A PS

The range includes models from 200 L and 300 L in energy efficiency Class A. Engineered to optimize energy consumption, ensuring minimal thermal losses due to Energy Efficiency Class A insulation.

*All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

The weights indicated in this website are net values for reference purposes only. Actual product weights may vary due to production tolerances.